



the market
leader

1



optical rear projection screen

window film | screen | advertize | signage



self-adhesive rear projection screen

옵티컬 리어 스크린 필름



www.novatec21.co.kr

제품 특징

180 ° 와이드 시야각, 2.2게인

- 리어스크린 : Self-adhesive optical rear projection screen
- 멀티 확산층 : Polyethylene terephthalate material with diffusion layer
- 스크린 특성 : 2.2 gain, 180 ° wide viewing angle
- 선명한 화질 : No "hot-spot" with higher contrast and color
- 유지관리 쉬움 : easy to clean and maintain



제품 사양

시선을 사로잡는 "유리 스크린" 필름

· 스크린 크기별 사양

단위 : mm

Model	Screen Diag. & Aspect Ratio	View Width	View Height	Gain	Screen Material	Self-Adhesive
iRP74V	74"(4:3)	1125	1500	2.2	Wraith Veil 2	Yes
iRP99V	99"(4:3)	1500	2000	2.2	Wraith Veil 2	Yes
iRP68V	68"(16:9)	844	1500	2.2	Wraith Veil 2	Yes
iRP103X-100H	103"/100(16:10/16:9)	1500	2210	2.2	Wraith Veil 2	Yes
iRP121H	121"(16:9)	1500	2666	2.2	Wraith Veil 2	Yes
iRP70X	70"(16:10)	938	1500	2.2	Wraith Veil 2	Yes
iRP112X	112"(16:10)	1500	2400	2.2	Wraith Veil 2	Yes
iRP151C	151"(2.35:1)	1500	3525	2.2	Wraith Veil 2	Yes
iRP10m	N/A	1500	10000	2.2	Wraith Veil 2	Yes



WraithVeil screen material is your perfect solution for your rear projection needs Gain: 2.2



WRAITH VEIL 2



Self-adhesive Optical Rear Projection Film





상점 쇼윈도, 리테일 POP, 전시장, 커피숍, 클럽, 홍보관, 기업체, 교육관련 시설 홍보등
Eye-catching " window-advertizing-screen "



Insta-RP[®] specifications

physical properties

Color	:	matte white
Thickness	:	145um±5um
Roll Width	:	1500mm±1%
Light transmittance	:	30%
Haze	:	70%
Recommend Tempertaure	:	-10 ~ 40
High temperature storage 60 ,72hr	:	pass
Low temperature storage -20 ,72hr	:	pass
Resistance to UV 15W x 24hr	:	pass
Flammability test classA	:	pass
GREEN GUARD	:	certificate

Installation

1. Partially separate the film from the screen's adhesive backing.
2. Water should be sprayed on glass and material before attaching material to the surface.
3. Carefully smooth out the surface (latex gloves are recommended).
4. Use the plastic scraper to eliminate all air bubbles, and or ripples.
5. Use the microfiber cleaning cloth to clean the surface.
6. Allow material to stand unused for 2 to 3 hours to bond and set.

Caution

1. This sensitive adhesive material is not re-useable. Attempting to remove after installed can damage the screen.
2. Make sure the permanent surface for the material is cleaned before installing.
3. Keep sharp objects away from the material. Punctures, scratches, or tears in the screen may distort the projected image.
4. Attempting to force the material to another part of the glass or acrylic surface may cause creases within the material.
5. If installed properly, any bubbles or ripples in the material will disappear within 2 to 3 days. (Bubbles or ripples will not distort the projected image.)



the market
leader

Novatec Incorporation reserves the right to make design changes or to withdraw any design without notice.
©2013 Novatec Incorporation. Printed in the Korea

(주) 노바텍 인코퍼레이션

walltalkers

옵티컬 리어 스크린 필름

www.novatec21.co.kr

call: 02.573.2450

novatec21@naver.com

consider the possibilities



7075WBR5061